

# 2M-2815NVD

## COLOR DOME CAMERA



ITEM	2M-2815NVD	
<b>Signal System</b>	NTSC	PAL
<b>Scanning System</b>	2: 1 Interlace	
<b>Scanning Freq' (H)</b>	15.734 KHz	15.625 KHz
<b>Scanning Freq' (V)</b>	59.94 Hz	50 Hz
<b>Image Sensor</b>	1/3" SONY Super HAD CCD	
<b>Sync. System</b>	Internal	
<b>Total Pixels Number</b>	811(H) x 508(V) 410K	795(H) x 596(V) 470K
<b>Effective Pixels Number</b>	768(H) x 494(V) 380K	752(H) x 582(V) 440K
<b>Resolution</b>	550 TV Lines	
<b>Video Output</b>	1.0 Vp-p (75Ω, Composite)	
<b>S/N Ratio</b>	More Than 50dB (AGC Off)	
<b>Digital Zoom Ratio</b>	2x (On/Off)	
<b>Lens</b>	DC Iris Vari-Focal Lens (f=2.9~10mm, F1.2)	
<b>Min. Illumination</b>	0.3Lux (Color) / 0.1Lux (B/W) / 0.008Lux (DSS x32, Color) / 0.001Lux (DSS x32, B/W)	
<b>Digital Noise Reduction (SDNR)</b>	Auto	
<b>White Balance</b>	Auto	
<b>DIP SW</b>	On/Off Switchable : AGC, BLC, Flickerless, D. Zoom, DSS On/Off, D/N	
<b>In/Out Connector</b>	Power, Video	
<b>Electronic Shutter Speed</b>	1/60~1/120,000sec	1/50~1/120,000sec
<b>Storage Temp.</b>	-20°C~65°C	
<b>Operating Temp.</b>	-10°C~45°C	
<b>Dimensions</b>	100(Ø) x 102(H) mm	
<b>Power Supply</b>	12VDC / 24VAC - Dual Power	
<b>Weight</b>	Approx. 366g	



### FEATURES

- High Sensitive 1/3" SONY SuperHAD CCD
- Built-in DC Iris Vari-Focal Lens (f=2.9~10mm)
- High Resolution: 550 TV Lines
- Day & Night (ICR)
- Electrical Sensitivity Enhancement (DSS)
- 2x Digital Zoom
- Min. Illumination: 0.008 Lux (DSS x32), 0.001 Lux (DSS x32 with ICR On)
- DIP SW (On/Off) : AGC, BLC, Flickerless
- 3-Axis Camera Bracket
- Dual Power - 12VDC / 24VAC

### DIMENSION

