

2M-B52IR

H.R. IR CAMERA



ITEM	2M-B52IR
Pick Up Element	1/3" HR Color CCD Image Sensor
Number of Pixel	768(H) x 494(V) - NTSC 752(H) x 582(V) - PAL
Resolution	520TV Lines
Minimum Illumination	0.3 Lux / F2.0, 0 Lux (IR On)
IR LED	35 Units
IR Effective Range	Up to 35 Meters
S/N Ratio	More Than 48dB (AGC Off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f6.0mm / F2.0
Lens Angle	54°
White Balance	ATW
AGC	Auto
IRIS Mode	AES
IP Rating	IP-67
Video Output	1.0Vp-p Composite, 75Ω
Operating Temperature	0°C~40°C
Power Source (±10%)	12VDC
Current Consumption (±10%)	90mA (IR Off); 450mA (IR On)
Dimensions (mm)	75(∅) x 142(H)
Weight (g) (±5%)	570



FEATURES

- Cable Management to Prevent Intentional Cable Damaging
- High Resolution of 520TV Lines
- High Sensitivity in the Dark Environment, 0.3 Lux / F2.0, 0 Lux (IR On)
- Day & Night Features for 24 Hour Surveillance
- IR Distance: Up to 35 Meters with 35 IR LEDs
- IP-67, Suitable for Outdoor Use

