

# 2M-D1760N

## COLOR DOME CAMERA



| ITEM                      | 2M-D1760N  |                   |
|---------------------------|--|-------------------|
| <b>Signal System</b>      | NTSC   | PAL               |
| <b>Scanning System</b>    | 2: 1 Interlace                                     |                   |
| <b>Scanning Freq' (H)</b> | 15.734 KHz   | 15.625 KHz        |
| <b>Scanning Freq' (V)</b> | 59.94 Hz   | 50 Hz             |
| <b>Image Sensor</b>       | 1/3" SONY Super HAD CCD                            |                   |
| <b>Sync. System</b>       | Internal   |                   |
| <b>Resolution</b>         | 480 TV Lines (Color)                               |                   |
| <b>Video Output</b>       | 1.0 Vp-p composite video at 75ohm                  |                   |
| <b>Lens</b>               | Fixed lens(f=3.8mm F2.0)                           |                   |
| <b>Min. Illumination</b>  | 0.3Lux   |                   |
| <b>Electronic Shutter</b> | 1/60~1/10,000 sec.                                 | 1/50~1/10,000 sec |
| <b>Focus</b>              | Manual   |                   |
| <b>White Balance</b>      | Auto   |                   |
| <b>In/Out Connector</b>   | Power input (Red jack), Video output (Yellow jack) |                   |
| <b>Power Consumption</b>  | 150mA / 1.8W(max.)                                 |                   |
| <b>Dimensions</b>         | 85(2) x 76.7(H) mm                                 |                   |
| <b>Weight</b>             | Approximately 220g                                 |                   |



### FEATURES

- 1/3" SONY Super HAD CCD
- Built-in Fixed Lens (f=3.8mm)
- 480 TV Lines
- Min. illumination: 0.3Lux
- Automatic White Balance
- Automatic Gain Control
- Back Light Comp'
- 85mm Dome Size

### DIMENSION

