

# 2M-DVR8700 Series

## 1280 x 1024 HD Display DVR



ITEM	2M-8704	2M-8708	2M-8716
<b>Channel &amp; Compression</b>	4 CH H.264	8 CH H.264	16 CH H.264
<b>Video Format</b>	NTSC / PAL		
<b>Video Input</b>	1.0Vp-p / 75Ω, BNC x 4	1.0Vp-p / 75Ω, BNC x 8	1.0Vp-p / 75Ω, BNC x 16
<b>Video Output</b>	1.0Vp-p / 75Ω, BNC x 1, VGA x 1		
<b>VGA Output Resolution</b>	1280 x 1024		
<b>D1 Recording Format</b>	100fps (PAL) / 120fps (NTSC)	50fps (PAL) / 60fps (NTSC)	100fps (PAL) / 120fps (NTSC)
<b>CIF Recording Format</b>	100fps (PAL) / 120fps (NTSC)	200fps (PAL) / 240fps (NTSC)	400fps (PAL) / 480fps (NTSC)
<b>D1 Playback Format</b>	25fps (PAL) / 30fps (NTSC)	50fps (PAL) / 60fps (NTSC)	100fps (PAL) / 120fps (NTSC)
<b>CIF Playback Format</b>	100fps (PAL) / 120fps (NTSC)	200fps (PAL) / 240fps (NTSC)	400fps (PAL) / 480fps (NTSC)
<b>Network Resolution / FPS</b>	CIF > 10fps For Each Channel		
<b>Audio</b>	RCA x 4 Input, RCA x 1 Output		
<b>Alarm Mode</b>	Disk Full Alarm, Motion Detection Alarm, Video Loss Alarm		
<b>Recording Mode</b>	Time / Motion Detection		
<b>Network Port</b>	100M RJ-45		
<b>USB Port</b>	Two USB 2.0 Host		
<b>Hard Disk</b>	1 x 2000G		
<b>DVD-RW</b>	USB DVD-RW		
<b>PTZ</b>	RS-485		
<b>Remote Control</b>	Yes		
<b>USB Mouse</b>	Yes		
<b>Power Supply</b>	220V / 110V		
<b>Operating Temperature</b>	-10°C + 50°C		
<b>Operating Humidity</b>	10% - 90%		
<b>Weight</b>	About 3kg With Package		
<b>Dimension</b>	338mm(L) x 250mm(W) x 65mm(H)		

### FEATURES

- VGA Output Resolution is 1280 x 1024
- Up to 16 Channels CIF Real-Time Recording and 16 Channels Playback at the Same Time
- 4CH DVR Support D1 Real-Time Recording, 8/16CH DVR Support D1 Non-Real-Time Recording, Each Channel is 6 Frames
- Supply Built-in DDNS Domain Name
- Support Five OS For Mobile Surveillance
- Powerful CMS
- Support 16 Users Network View Simultaneously



**H.264**



**Mobile Surveillance**



**CMS**



**VGA**