

MON201CL

20-inch Color LCD Flat Panel Display Monitor



Security Systems



- 500 TVL Resolution
- Loop-through Composite Video, Y/C (S-video) and Audio Inputs
- Analog VGA Input 800 x 600 Max. Software Scalable to 1024 x 768
- NTSC & PAL Formats
- Universal Power Source
- Front Panel Control Lockout
- On-screen Display (OSD) for Setup and Adjustment
- 12 VDC Power Outlet for Public View Monitoring

Designed for the CCTV security marketplace, the MON201CL monitor includes two looping composite video inputs, two looping audio inputs, and one looping Y/C input. Additionally, this model includes an analog VGA input to accommodate the increasing use of 'PCs' and digital video devices in security applications.

The MON201CL has been tested for compatibility of operation with analog output devices such as the Allegiant Matrix Switcher System, the Divar Digital Recorder, and standard multiplexers. It is also recommended for use with devices and systems with VGA output of 800 x 600 maximum resolution. In addition, in applications where required, the MON201CL is scalable via on-board software to be compatible with a 1024 x 768 resolution VGA source.

The versatile design allows it to automatically accept NTSC and PAL signal formats, and power supply voltages from 96 to 256 VAC. When connected to multiplexer devices, the underscan function provides a multi-screen display of individual cameras without loss or distortion of images.

Its compact styling, including an LCD panel width of 86 mm (3.4 in.) and wide range viewing angle, makes the MON201CL an excellent choice for space limited and public view applications. Specific features to support public view monitoring include a DC power outlet for a 12 VDC camera; user friendly on-screen menus accessible via front panel controls or a remote control transmitter; and a front panel lockout feature to prevent access once monitor set up is completed.

Electrical	
Rated Voltage	120/230 VAC, 50/60 Hz
Voltage Range	96 to 256 VAC
Power at Rated Voltage	55 W
Sync Format	Auto-sensing
NTSC	525 lines, 60 fields/s
PAL	625 lines, 50 fields/s
LCD Panel	TFT LCD
Screen Size H x V:	408 x 306 mm (16.1 x 12.0 in.)
Viewable Picture Area	51 cm (20.1 in.), measured diagonally
Pixel Pitch H x V:	0.51 x 0.51 mm
Resolution	500 TVL
Aspect Ratio	4:3
Display Colors	16.8 million colors
Response Time	16 ms
Backlight	Four (4) cold cathode fluorescent tubes, rated life 50,000 hours, at 50% brightness
Optical Characteristics	
Luminance	500 cd/m ²
Contrast Ratio	500:1
Viewing Angle	160° horizontal, 160° vertical
Video Input	
Composite Video (CVBS)	1.0 Vp-p (0.5-2.0 Vp-p), automatic switching from 75 Ω unbalanced termination to Hi-Z with loop-through operation
Y/C (S-video)	1.0 Vp-p (0.5-2.0 Vp-p), automatic switching from 75 Ω unbalanced termination to Hi-Z with loop-through operation
VGA Input	
Analog RGB	0.707 Vp-p/75 Ω
VGA Timing Modes	640 x 480 60/72/75 Hz 800 x 600 56/70/72/75 Hz 1024 x 768 60 Hz (scalable)
Audio Input	Level: 1.0 Vp-p/1 kHz
Audio Output	Loop-through line level Speaker: two (2), 4 W

Controls	
Front Panel	Push-button
Input	Select CVBS 1, CVBS 2, Y/C, or VGA Input
Menu	Selects on-screen display (OSD)
Select	Selects sub-menu item
Adjust	◀ Adjustment decrease ▶ Adjustment increase
Power	On/Off
Front Panel Lockout	Select from <i>General</i> OSD menu
Remote Control	Controls monitor functions
On-screen Display	
General	Language, backlight, power-on option, key lock, volume, treble, bass balance
Video	Brightness, contrast, color, tint (NTSC only), sharpness, color temperature, video system, comb filter, scan mode, display, default
VGA	Auto, brightness, contrast, H-position, V-position, clock, phase, color temperature, white balance, display, default
Indicators	
LED	Power-on (Green), standby, (Amber)
On-screen	Video loss
Connectors	
Input 1	Composite Video: two (2) BNC (1 in, 1 out) Audio: four (4) RCA (2 in, 2 out; left, right)
Input 2	Composite Video: Two (2) BNC (1 in, 1 out) Audio: four (4) RCA (2 in, 2 out; left, right)
Y/C (S-video)	Two (2) mini-DIN, 4-pin (1 in, 1 out)
VGA	One (1) 15-pin D-sub
DC Power Output	Bayonet connector, 12 VDC regulated, 500 mA
Power Cord	Two (2), 3-wire with grounded plug, 1.8 m (6 ft) long; one (1) with European continental plug type and one (1) with U.S. plug type

Mechanical	
Cabinet	Material: metal
	Finish: charcoal
	Wall-mounting: compatible with VESA standard bracket, 100 mm centers
Dimensions	
LCD Panel with Base	W x D x H: 461 x 178 to 229 x 397 mm (18.12 x 7 to 9 x 15.62 in.)
LCD Panel Only	W x D x H: 461 x 86 x 397 mm (18.12 x 3.38 x 15.62 in.)
Weight	7.3 kg (16.1 lb)
Environmental	
Temperature	Operating: 0°C to +60°C (+32°F to 140°F) Storage: -20°C to +60°C (-4°F to 140°F)
Humidity	10% to 95%, noncondensing
Product Regulatory Compliance	
Electromagnetic Compatibility (EMC)	
	Complies with FCC Part 15, ICES-003, and CE regulations
Product Safety	Complies with CE regulations, UL, cUL, EN, and IEC standards

Allegiant and Divar are registered by Bosch Security Systems, Inc. in the US Patent & Trademark Office.

Americas

Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 (585) 223 4060
+1 800 289 0096
security.sales@us.bosch.com
<http://www.boschsecurity.us>

Europe, Middle East, Africa

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
emea.securitysystems@bosch.com
<http://www.boschsecurity.com>

Asia-Pacific

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
<http://www.boschsecurity.com>

BOSCH