



Front panel controls including A/B video input selector

## 14" Color CRT Monitor



# SAM-14XL

400 TV LINE RESOLUTION CRT

- NTSC/PAL selection system
- VIDEO A/B, Y/C input selector control
- VIDEO A/B input/output looping with automatic 75ohms termination
- Y/C input/output looping with impedance selector for high impedance/75ohms
- Recessed carrying handle
- Built-in comb filter
- Universal power- 100 ~ 240 VAC

# SAM-14XL

## SPECIFICATIONS

Picture Tube: 14-inch Diagonal, 90 Deflection Angle  
(useful screen size: 13.3")

Power Source: 100V-240V AC 50/60Hz 1.2A

Power Consumption: 70 Watts

Format: NTSC or PAL standard

Resolution: 400 TV lines at center(NTSC)  
350 TV lines at center(PAL)  
420 TV lines at center(Y/C)

Video Input Impedance: NTSC/PAL 1.0Vp-p, 75ohms, negative sync(BNC)

Input Signal: Video A,B: Composite Video 1.0Vp-p(at 75ohm)  
negative sync(BNC)  
Video Y/C: 1.0Vp-p(Y), 0.3Vp-p(C), 75ohms(Y/C)  
Audio: 300m Vrms

Output Signal Video A,B: Composite Video 1.0Vp-p(at 75ohm)  
negative sync(BNC)  
Video Y/C: 1.0Vp-p(Y), 0.3Vp-p(C), 75ohms(Y/C)

Audio: 300m Vrms

Ambient Temperature: 0° ~ +40° (32°~95°)

Ambient Humidity: 10%~90% (non-condensing)

Dimension(WxHxD): 350mm x 330mm x 375mm  
(13.8inch x 13inch x 14.8inch)

Weight: 30 lbs.(14 Kg.)



[www.samsung360.com](http://www.samsung360.com)

Design and specifications are subject to change without notice.



175 Pinelawn Rd., Suite 210, Melville NY 11747  
Tel: 631-249-0600 Fax: 631-249-0603

DISTRIBUTED BY



DS-SAM-14XL-0107