



# VEILUX®

## NORMAL RESOLUTION DAY & NIGHT MINI DOME CAMERA

### SVD-48MINI



MIRROR FUNCTION **BB**

0.01 LUX

BLC Back Light Compensation  
OFF ON

VOLTAGE 12DC

480 TV LINES

### SPECIFICATIONS

ITEM	SVD-48MINI	
TV System	NTSC	PAL
Image Sensor	1/3" SONY SuperHAD CCD	
Effective Pixels	(H)537 x (V)505	(H)537 x (V)597
Electronic Shutter	1/60~1/120,000 sec.	1/50~1/120,000 sec.
Scanning System	2 : 1 Interlace	
Synchronization	Internal	
Resolution	480TV Lines	
Min. Illumination	0.01Lux (f1.2 20IRE)	
y Correction	0.45	
Video Output	1.0Vp-p Composite Video at 75ohm	
S/N Ratio	More Than 50dB (AGC OFF)	
White Balance	ATW / AWC / Manual	
BLC	OFF / WIDE BLC	
Gain Control	Low / Middle / High / OFF	
Motion Detection	ON / OFF	
Privacy Masking	ON / OFF (4 Areas)	
Mirror	ON / OFF	
Day & Night	Color / B/W / Auto / EXT	
Operating Temp' / Humidity	-20°C ~ 60°C / 30%~80%	
Storage Temp' / Humidity	-30°C ~ 60°C / 20%~90%	
Power Supply	12VDC / 200mA (Max)	
Dimensions	100mm(ø) x 68mm(H)	

### FEATURES

- 1/3" SONY SuperHAD CCD
- High Resolution (Color: 480TV Lines, B/W: 600TV Lines)
- Day & Night
- Controlled By OSD Menu (Multi-Languages)
- Stabilized Images By Reducing Flickering
- LSC (Lens Shading Compensation)
- WIDE BLC
- Privacy Masking and Motion Detection For Up to 4 Areas
- 3-Axis Moving Bracket



**VEILUX®**  
*The Art of Surveillance*