



VEILUX®

16 CHANNEL VIDEO CAPTURE BOARD

VCB-120-16

SPECIFICATIONS

ITEM	VCB-120-16
Camera Inputs	16 Channel
Frame Rate for Monitoring	Live Display 480 FPS (NTSC) / 400 FPS (PAL)
Frame Rate for Recording	Max. 120 FPS (NTSC) / 100 FPS (PAL)
Compression Algorithm	MJEG, M-MPEG, H.264 (Selectable)
Image Size (Resolution)	NTSC (320 x 240), (640 x 240), (640 x 480) PAL (352 x 288), (704 x 288), (704 x 576)
System CPU	P4 - 2.0GHz
Analog TV Output	Yes
No. of Sensor Input	16 Channel
No. of Alarm Output	4
P/T/Z Camera Control	Yes
Network for Remote	TCP/IP Based Network, LAN, PSTN, ISDN
Remote Control	Setting, Display Control, Relay Output, P/T/Z Camera
Remote Transmission	View, Playback, Notification, 2-Way Audio
Watchdog	Yes
Time Date Stamp	Yes
Multi-Users Control	Yes (By Registration)
Audio Record	16 Channel
Image Authentication	Yes
Data Back Up	DVD, DAT, HDD, CD-RW
Case	19" Rack Mount Type Case or Standard PC Case
Operation System	Windows 2000, XP, 2003
Slot Type (Interface)	PCI
5VDC Input	No
To Use 2-Cards	Yes



IMAGE



VEILUX®

The Art of Surveillance