

2MVSC-4000B

2M Solar Camera Trailer



Features

Axle	Single	Number of Dome Cameras	1
Tire and Rim Size	MAXXIS A/T R15	Bullet Camera Specs	3MP, HD IR50m
Outrigger	Manual	Dome Camera Specs	2MP HD, 20x Optical Zoom, IR150m, 360° View
Tow Hitch	50 mm Ball 4412LBS	No. of Solar Panels	3
Mast Raise/Extension	Manual	Panel Wattage	300W
Mast Height m/ft	9m/29'6"	Panel Output	900W
Mast Rotation	Option	Panel Material	Microcrystal Silicon
Wind Rating Speed	100kph	Controller	Morningstar/Other MPPT
Width	1775mm/5'10"	Model	CNK 150
Length	4020mm/13'2"	No. of Battery	6
Height	3240mm/10'8"	Capacity	150AH
Weight	1330Kg/2932Lb	Voltage	DC 12V
Number of Cameras	4 HD 1080P Cameras	Material	Colloid
Number of Bullet Cameras	3		

Specifications

MODEL 2MVSC-4000B	
SPECIFICATION	
Product Name	Solar CCTV Trailer
Usage	Outdoor Mobile Monitoring
Brand	Valiant
PERFORMANCE	
Run Time	Continuous discharge time of 216 hours when fully charged
Charge Time	15hr
Wind Rating Speed	100kph
Protection Level	IP65
DIMENSION AND WEIGHT	
Size (not including mast)	4020x1775x2150
Weight	1330KGS
20' Container Can Be Fit	4 sets
SOLAR PANEL AND BATTERY	
Solar Panel	300Wx3 monocrystalline silicon
Battery	150AHx6 free maintenance
Camera and Mast	
Dome Camera	1x 2M Technology PTZ Camera
Bullet Camera	3x 2M Technology Bullet Camera
Mast Height	9 meters
TRAILER	
Axle	Single
Axle	Maxxis A/T R15
Axle	A-type drawbar with grating plate
Axle	Bump Brake (pintle ring hitch/50mm ball hitch) & brake disc assembly & wheel chock
Axle	Double Eye Leaf Spring
Axle	ADR Standard
Outrigger	7000LBS Jack and High Stregth Square Tube
Fire Extinguisher	SAI/EN3/CE Certification
ELECTRICAL PARTS	
Fire Extinguisher	US Morningstar MPPT/Chinese MPPT
Breaker, Relay, Switch, PV Cable and Connector, etc.	All electrical parts have UL Certification
GPS	Option
OTHER	
Packing	Plywood Case/Wooden Case/EPE Foam
WARRANTY	Camera: 1 year or 2500 hours, whichever comes first Trailer: 3 years or 7500 hours, whichever comes first