



## Specifications

CAMERA	
<b>Image Sensor</b>	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
<b>Image Resolution</b>	2M: 1920 x 1080
<b>TV System</b>	PAL / NTSC
<b>Electronic Shutter</b>	AUTO / MANUAL
<b>Scanning System</b>	Progressive Scan
<b>Video Output Mode</b>	AHD/TVI/CVI: 2M@30fps/25fps
LENS	
<b>Focus Length</b>	2.7-13.5mm Motor Zoom
<b>Focus Control</b>	Auto
<b>Lens Type</b>	Auto
NIGHT VISION	
<b>IR Cut Filter</b>	YES
<b>Infrared LED</b>	42μ x 4PCS
<b>Infrared Distance</b>	30M
<b>IR Status</b>	AGC Auto Control
CAMERA	
<b>Starlight</b>	YES
<b>Day/Night</b>	YES
<b>OSD Menu</b>	YES
<b>WDR</b>	YES
<b>UTC</b>	YES
<b>Noise Reduction</b>	3DNR
<b>White Balance</b>	AUTO / MANUAL
<b>Gain Control</b>	AUTO
GENERAL	
<b>Housing</b>	Metal, IP67
<b>Bracket</b>	NO
<b>Operation Temperature</b>	-10°C ~ 60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ 60°C RH95% Max
<b>Power Source</b>	DC12V ± 10%, 750mA
<b>Dimension</b>	Φ142 x 142(H) mm
<b>Weight</b>	2.65 lbs

## Features

### Features:

- 1/2.8" SONY Starvis Back-illuminated CMOS Sensor
- TVI/AHD/CVI/CVBS 4-IN-1
- 2.7-13.5mm Motorized Lens
- IR Distance Max. 30m
- IP66 Outdoor, OSD & UTC Support

## Dimensions

