



Specifications

| CAMERA | |
|------------------------------|--|
| Video Output Mode | AHD/TVI/CVI: 2M@30fps/25fps |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Image Resolution | 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | AUTO / MANUAL |
| Scanning System | Progressive Scan |
| LENS | |
| Focus Length | 2.7-13.5mm Motor Zoom |
| Focus Control | Auto |
| Lens Type | Auto |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42μ x 4PCS |
| Infrared Distance | 40M |
| IR Status | AGC Auto Control |
| General | |
| Housing | Metal, IP67 |
| Bracket | NO |
| Operation Temperature | -10°C~ +60°C RH95% Max |
| Storage Temperature | -20°C~ +60°C RH95% Max |
| Power Source | DC12V±10%, 750mA |
| Dimension | Φ136 x 148(H) (mm) |
| Weight | 3.75 lbs |

Features

Features:

- 1/2.8"SONY Starvis Back-illuminated CMOS sensor
- 4-IN-1 Signal (TVI/AHD/CVI/CVBS)
- 2.7-13.5mm Motorized Lens
- IR Distance max 40m
- IP67 outdoor, OSD&UTC support